



## XT3215



### KEY FEATURES

- Intel D525 / 1.8 GHz dual core
- 2 GB DDR3 memory (4GB maximum)
- Resistive Touch
- Fan Free
- Dual Gigabit LAN
- Digital Brightness Control
- VESA Mount Capability
- Slim, folding base design
- Optional Solid State Drive and WiFi

#### About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

### Flexible, Cost-Effective Workhorse

The XT3215 is designed for environments when cost and performance is a critical factor. Even though the XT3215 has exceptional price / performance, its quality has a foundation in the long legacy of Posiflex field-tested reliability.

The XT3215 base folds and configures to an optimal angle and space. The low-profile design fits in the tightest of spaces, reducing shipping costs up to 40%. With this sleekly designed fan-free exterior comes the Intel D525 1.8 GHz dual core power to run many applications for hospitality, retail, health care and more.

The XT3215 features an Intel D525 1.8 GHz dual core, 2GB standard DDR3 RAM (4 GB maximum) and a 15" resistive touch TFT LCD touch screen terminal. Along with a rich array of connectivity features are options for a mini-PCIe slot for WiFi and VESA wall mount bracket.

## XT3215

Specifications	XT3215
Processor	Intel D525 / 1.8 GHz / 1M Cache (dual core)
System Memory	DDR3 800MHz SO-DIMM x 1, max. 4GB, factory default 2GB
Storage Device	SATA Storage x 2, factory default 320GB HDD x 1
Supported OS	POSReady 2009 / Windows 7 / POSReady 7 / Linux per request
Touch	Resistive
Physical Dimensions	
Dimensions (WxDxH) in.	14.6" x 12.6" x 9.9"
Display	15" LCD with 1024x768 resolution
Weight (lbs)	12.3
Connectivity	
LAN Port	10 / 100 / 1000 Mb x 2
Serial Port	4, DB9 x 3 + RJ45 x 1, 5V / 12V support on all COM ports
VGA Port	VGA x 1, 12V support for Posiflex monitors
Standard USB Port	5 (4 on I/O panel, 1 on side)
Mini-PCIe slot	Optional
CR Port	1, control 2 CR via optional Y-cable
Options	
SSD	
Parallel Port with optional extension cable	
WB-5000 wall mount bracket	
WiFi	
Peripherals	
MSR w/ Optional Finger Print	SA100, SA300
Pole Display	PD2604 (Rear Mount)
Secondary Monitor	12" LM2312
Printer	PP9000
Cash	CR6300, CR3100

\*\* The product information and specifications are subject to change without prior notice.



PD2604



PP9000  
 USB + Optional Serial,  
 Parallel, LAN or Wireless



CR3100  
 Adjustable Coin Slot  
 15.7" W x 16.3" D x 3.5" H